

RADIAL DRILLING MACHINE



Make : *MAS*

Type : *VO50-1250*

Year : *1981*

Specifications :

<i>Max. drilling diameter</i>	<i>50 mm (steel)</i>
<i>Max. drilling diameter</i>	<i>60 mm (cast iron)</i>
<i>Arm vertical stroke</i>	<i>875 mm</i>
<i>Arm orientation on column</i>	<i>0° to 180°</i>
<i>Min. / max. distance between spindle and base</i>	<i>320 / 1 505 mm</i>
<i>Min. / max. distance between spindle axis and column guiding</i>	<i>320 / 1 600 mm</i>
<i>Min. / max. circle of holes to drill</i>	<i>1 208 / 3 735 mm</i>
<i>Spindle stroke</i>	<i>310 mm</i>
<i>Spindle taper</i>	<i>No 5 MT</i>
<i>Spindle diameter</i>	<i>55 mm</i>
<i>Spindle speed (16 ranges)</i>	<i>28 - 2 500 RPM</i>
<i>Spindle feed rates (16 ranges)</i>	<i>0,05 - 2 mm/rev</i>
<i>Useful area of base</i>	<i>1 145 x 3 100 mm</i>
<i>Machine height</i>	<i>3 396 mm</i>
<i>Machine weight</i>	<i>4 300 kg</i>

These specifications are given in good faith and are correct to the best of our knowledge. Details are not binding.